

LVT DRYBACK | 2.5 MM TOTAL THICKNESS | 0.55 MM WEAR LAYER | 153 × 765 MM



153 × 765 mm (6.02 × 30.12 in) | 2.5 mm total thickness | 0.55 mm wear layer

Prepared by Ecoflors Technical Team

Version: 2026.08.31-R03

<https://ecoflors.com/>

PRODUCT CONFIGURATION			PACKING & WEIGHT DATA		
CHARACTERISTIC	STANDARD / UNIT	SPECIFICATION	PACKING ITEM	UNIT / BASIS	VALUE
Product type	—	LVT Dryback Herringbone Flooring	Carton packing	pcs / carton	36 pcs/carton
Product format	—	Herringbone	Carton dimensions	mm / in	161.0 × 773.0 × 92.0 mm (6.34 × 30.43 × 3.62 in)
Dimensions	mm / in	153 × 765 mm (6.02 × 30.12 in)	Carton coverage	m ² / sq ft	4.213 m ² /carton (45.36 sq ft/carton)
Total thickness	mm	2.5 mm	Estimated carton net weight	kg / lb	20.01 kg/carton (44.12 lb/carton)
Wear layer	mm / mil	0.55 mm (≈22 mil)	Estimated carton gross weight	kg / lb	20.51 kg/carton (45.23 lb/carton)
Construction	—	UV coating + wear layer + décor film + LVT middle and bottom layers; no fiberglass layer	Pallet packing	cartons / pallet	72 cartons/pallet
Surface texture	—	EIR (embossed-in-register)	Pallet configuration	cartons × layers	12 cartons/layer (6 cartons/row × 2 rows) × 6 layers
Surface treatment	—	UV-cured matte finish (gloss level: 4–6 GU)	Pallet coverage	m ² / sq ft	303.380 m ² /pallet (3265.56 sq ft/pallet)
Installation method	—	Glue-down installation	Loaded pallet dimensions	mm / in	990 × 1560 × 687.0 mm (38.98 × 61.42 × 27.05 in)
Bevel	—	4-sided micro bevel	Estimated pallet net weight	kg / lb	1441.06 kg/pallet (3176.99 lb/pallet)
Classification	ISO 10874	Class 34 — also suitable for Class 33 applications	Estimated pallet gross weight	kg / lb	1481.06 kg/pallet (3265.17 lb/pallet)
Residential service life	years	25+ years	Maximum pallet loading	pallets / 20 ft GP	16 pallets/20 ft GP (up to 3-high stacking)
Commercial service life	years	15+ years	Coverage per 20 ft GP	m ² / sq ft	4854.090 m ² /20 ft GP (52248.99 sq ft/20 ft GP)
			Estimated total cargo gross weight per 20 ft GP	kg / lb	23,696.93 kg/20 ft GP (52,242.78 lb/20 ft GP)