

LVT DRYBACK | 2.5 MM TOTAL THICKNESS | 0.55 MM WEAR LAYER | 228.6 × 1524 MM



228.6 × 1524 mm (9.00 × 60.00 in) | 2.5 mm total thickness | 0.55 mm wear layer

Prepared by Ecoflors Technical Team

Version: 2026.08.31-R03

<https://ecoflors.com/>

PRODUCT CONFIGURATION			PACKING & WEIGHT DATA		
CHARACTERISTIC	STANDARD / UNIT	SPECIFICATION	PACKING ITEM	UNIT / BASIS	VALUE
Product type	—	LVT Dryback Plank Flooring	Carton packing	pcs / carton	12 pcs/carton
Product format	—	Straight plank	Carton dimensions	mm / in	236.6 × 1534.0 × 32.0 mm (9.31 × 60.39 × 1.26 in)
Dimensions	mm / in	228.6 × 1524 mm (9.00 × 60.00 in)	Carton coverage	m ² / sq ft	4.180 m ² /carton (45.00 sq ft/carton)
Total thickness	mm	2.5 mm	Estimated carton net weight	kg / lb	19.86 kg/carton (43.78 lb/carton)
Wear layer	mm / mil	0.55 mm (≈22 mil)	Estimated carton gross weight	kg / lb	20.36 kg/carton (44.88 lb/carton)
Construction	—	UV coating + wear layer + décor film + LVT middle and bottom layers; no fiberglass layer	Pallet packing	cartons / pallet	68 cartons/pallet
Surface texture	—	EIR (embossed-in-register)	Pallet configuration	cartons × layers	4 cartons/layer × 17 layers
Surface treatment	—	UV-cured matte finish (gloss level: 4–6 GU)	Pallet coverage	m ² / sq ft	284.283 m ² /pallet (3060.00 sq ft/pallet)
Installation method	—	Glue-down installation	Loaded pallet dimensions	mm / in	970 × 1550 × 679.0 mm (38.19 × 61.02 × 26.73 in)
Bevel	—	4-sided micro bevel	Estimated pallet net weight	kg / lb	1350.35 kg/pallet (2977.00 lb/pallet)
Classification	ISO 10874	Class 34 — also suitable for Class 33 applications	Estimated pallet gross weight	kg / lb	1390.35 kg/pallet (3065.19 lb/pallet)
Residential service life	years	25+ years	Maximum pallet loading	pallets / 20 ft GP	17 pallets/20 ft GP (up to 3-high stacking)
Commercial service life	years	15+ years	Coverage per 20 ft GP	m ² / sq ft	4832.816 m ² /20 ft GP (52020.00 sq ft/20 ft GP)
			Estimated total cargo gross weight per 20 ft GP	kg / lb	23,635.88 kg/20 ft GP (52,108.19 lb/20 ft GP)