

LVT DRYBACK | 3.0 MM TOTAL THICKNESS | 0.70 MM WEAR LAYER | 184.15 × 1219.2 MM



184.15 × 1219.2 mm (7.25 × 48.00 in) | 3.0 mm total thickness | 0.70 mm wear layer

Prepared by Ecoflors Technical Team

Version: 2026.09.09-R01

<https://ecoflors.com/>

PRODUCT CONFIGURATION			PACKING & WEIGHT DATA		
CHARACTERISTIC	STANDARD / UNIT	SPECIFICATION	PACKING ITEM	UNIT / BASIS	VALUE
Product type	—	LVT Dryback Plank Flooring	Carton packing	pcs / carton	18 pcs/carton
Product format	—	Straight plank	Carton dimensions	mm / in	192.2 × 1229.2 × 56.0 mm (7.56 × 48.39 × 2.20 in)
Dimensions	mm / in	184.15 × 1219.2 mm (7.25 × 48.00 in)	Carton coverage	m ² / sq ft	4.041 m ² /carton (43.50 sq ft/carton)
Total thickness	mm	3.0 mm	Estimated carton net weight	kg / lb	23.04 kg/carton (50.78 lb/carton)
Wear layer	mm / mil	0.70 mm (≈28 mil)	Estimated carton gross weight	kg / lb	23.54 kg/carton (51.89 lb/carton)
Construction	—	UV coating + wear layer + décor film + LVT middle and bottom layers; no fiberglass layer	Pallet packing	cartons / pallet	50 cartons/pallet
Surface texture	—	Wood texture	Pallet configuration	cartons × layers	5 cartons/layer × 10 layers
Surface treatment	—	Ultimate Shield — scratch-, stain- and wear-resistant surface coating; UV-cured matte finish (gloss level: 4–6 GU)	Pallet coverage	m ² / sq ft	202.064 m ² /pallet (2175.00 sq ft/pallet)
Installation method	—	Glue-down installation	Loaded pallet dimensions	mm / in	980 × 1240 × 695.0 mm (38.58 × 48.82 × 27.36 in)
Bevel	—	4-sided micro bevel	Estimated pallet net weight	kg / lb	1151.77 kg/pallet (2539.21 lb/pallet)
Classification	ISO 10874	Class 34 — Very heavy commercial use	Estimated pallet gross weight	kg / lb	1191.77 kg/pallet (2627.39 lb/pallet)
Residential service life	years	25+ years	Maximum pallet loading	pallets / 20 ft GP	20 pallets/20 ft GP (up to 3-high stacking)
Commercial service life	years	15+ years	Coverage per 20 ft GP	m ² / sq ft	4041.282 m ² /20 ft GP (43500.00 sq ft/20 ft GP)
			Estimated total cargo gross weight per 20 ft GP	kg / lb	23,835.31 kg/20 ft GP (52,547.86 lb/20 ft GP)