

PRODUCT CONFIGURATION			PACKING & WEIGHT DATA		
CHARACTERISTIC	STANDARD / UNIT	SPECIFICATION	PACKING ITEM	UNIT / BASIS	VALUE
Product type	—	SPC Rigid Core Click Flooring	Carton packing	pcs / carton	24 pcs/carton (A or B packed separately)
Product format	—	Herringbone A/B	Carton dimensions	mm / in	122.0 × 625.0 × 146.0 mm (4.80 × 24.61 × 5.75 in)
Dimensions	mm / in	110 × 610 mm (4.33 × 24.02 in)	Carton coverage	m ² / sq ft	1.610 m ² /carton (17.33 sq ft/carton)
Total thickness	mm	6.0 mm	Estimated carton net weight	kg / lb	16.27 kg/carton (35.86 lb/carton)
SPC core thickness	mm	5.0 mm	Estimated carton gross weight	kg / lb	16.77 kg/carton (36.96 lb/carton)
Attached underlay	mm	1.0 mm IXPE	Pallet packing	cartons / pallet	48 cartons/pallet
Wear layer	mm / mil	0.55 mm (≈22 mil)	Pallet configuration	cartons × layers	8 × 2 cartons/layer × 3 layers
Construction	—	5.0 mm SPC core + 1.0 mm IXPE underlay	Pallet coverage	m ² / sq ft	77.299 m ² /pallet (832.04 sq ft/pallet)
Surface texture options	—	Natural wood-grain texture, EIR (embossed-in-register) or crystal embossing	Loaded pallet dimensions	mm / in	1000 × 1270 × 573.0 mm (39.37 × 50.00 × 22.56 in)
Surface treatment	—	UV-cured matte finish (gloss level: 4–6 GU)	Estimated pallet net weight	kg / lb	780.72 kg/pallet (1721.20 lb/pallet)
Installation method	—	Floating installation	Estimated pallet gross weight	kg / lb	820.72 kg/pallet (1809.38 lb/pallet)
Click system options	—	Licensed Uniclic®, i4F or G2 system available	Maximum pallet loading	pallets / 20 ft GP	24 pallets/20 ft GP (up to 3-high stacking)
Bevel options	—	4-sided micro bevel or printed V-bevel available	Coverage per 20 ft GP	m ² / sq ft	1855.180 m ² /20 ft GP (19969.00 sq ft/20 ft GP)
Classification	ISO 10874	Class 33 — Commercial use	Estimated total cargo gross weight per 20 ft GP	kg / lb	19,697.33 kg/20 ft GP (43,425.17 lb/20 ft GP)
Residential service life	years	25+ years			
Commercial service life	years	15+ years			