SPC WALL TILE | 2.5 MM | 0.20 MM WEAR LAYER | 305 × 610 MM

ESSENTIAL • SKU EF-WT-ESS25-020-305610 • INTERIOR WALL USE

Prepared by Ecoflors Technical Team • Version 2026.11.04-R01 • ecoflors.com

PRODUCT SPECIFICATION

Product type	SPC Wall Tile
Product format	Wall tile
Intended application	Interior decorative wall covering
Dimensions	305 × 610 mm (12.01 × 24.02 in)
Panel area	0.1860 m²/panel (2.00 sq ft/panel)
Total thickness	2.5 mm
Wear layer	0.20 mm (≈8 mil)
Construction	UV coating + 0.20 mm wear layer + décor film + SPC rigid core
Edge profile	Straight edge standard
Installation method	Glue-down installation
Calculated panel net mass	0.93 kg/panel (2.05 lb/panel)

PACKING & LOADING REFERENCE

Packing format	Cartons on pallets
Carton packing	25 pcs/carton
Carton coverage	4.651 m²/carton (50.07 sq ft/carton)
Carton dimensions	317 × 625 × 64.5 mm (12.48 × 24.61 × 2.54 in)
Calculated carton net weight	23.26 kg/carton (51.27 lb/carton)
Calculated carton gross weight	23.76 kg/carton (52.37 lb/carton)
Pallet configuration	2 cartons/layer × 8 layers
Pallet packing	16 cartons / 400 panels per pallet
Loaded pallet dimensions	650 × 640 × 651.0 mm (25.59 × 25.20 × 25.63 in)
Pallet coverage	74.420 m²/pallet (801.05 sq ft/pallet)
Calculated pallet gross weight	412.10 kg/pallet (908.52 lb/pallet)
20 ft GP loading reference	60 pallets / 4465.200 m²/20 ft GP (48063.01 sq ft/20 ft GP)
20 ft GP cargo gross weight	24726.00 kg/20 ft GP (54511.50 lb/20 ft GP)