SPC WALL TILE | 2.5 MM | 0.20 MM WEAR LAYER | 610 × 1220 MM

ESSENTIAL • SKU EF-WT-ESS25-020-6101220 • INTERIOR WALL USE

Prepared by Ecoflors Technical Team • Version 2026.11.04-R01 • ecoflors.com

PRODUCT SPECIFICATION

Product type	SPC Wall Tile
Product format	Wall tile
Intended application	Interior decorative wall covering
Dimensions	610 × 1220 mm (24.02 × 48.03 in)
Panel area	0.7442 m²/panel (8.01 sq ft/panel)
Total thickness	2.5 mm
Wear layer	0.20 mm (≈8 mil)
Construction	UV coating + 0.20 mm wear layer + décor film + SPC rigid core
Edge profile	Straight edge standard
Installation method	Glue-down installation
Calculated panel net mass	3.72 kg/panel (8.20 lb/panel)

PACKING & LOADING REFERENCE

Packing format	Cartons on pallets
Carton packing	6 pcs/carton
Carton coverage	4.465 m²/carton (48.06 sq ft/carton)
Carton dimensions	622 × 1235 × 17.0 mm (24.49 × 48.62 × 0.67 in)
Calculated carton net weight	22.33 kg/carton (49.22 lb/carton)
Calculated carton gross weight	22.83 kg/carton (50.32 lb/carton)
Pallet configuration	1 cartons/layer × 33 layers
Pallet packing	33 cartons / 198 panels per pallet
Loaded pallet dimensions	640 × 1250 × 696.0 mm (25.20 × 49.21 × 27.40 in)
Pallet coverage	147.351 m²/pallet (1586.08 sq ft/pallet)
Calculated pallet gross weight	776.76 kg/pallet (1712.46 lb/pallet)
20 ft GP loading reference	32 pallets / 4715.251 m²/20 ft GP (50754.54 sq ft/20 ft GP)
20 ft GP cargo gross weight	24856.26 kg/20 ft GP (54798.66 lb/20 ft GP)