SPC WALL TILE | 4.0 MM | 0.20 MM WEAR LAYER | 305 × 610 MM

PREMIUM • SKU EF-WT-PRE40-020-305610 • INTERIOR WALL USE

Prepared by Ecoflors Technical Team • Version 2026.11.04-R01 • ecoflors.com

PRODUCT SPECIFICATION

Product type	SPC Wall Tile
Product format	Wall tile
Intended application	Interior decorative wall covering
Dimensions	305 × 610 mm (12.01 × 24.02 in)
Panel area	0.1860 m²/panel (2.00 sq ft/panel)
Total thickness	4.0 mm
Wear layer	0.20 mm (≈8 mil)
Construction	UV coating + 0.20 mm wear layer + décor film + SPC rigid core
Edge profile	Straight edge standard; 2-side T&G optional
Installation method	Glue-down installation (straight edge and optional T&G)
Calculated panel net mass	1.49 kg/panel (3.28 lb/panel)

PACKING & LOADING REFERENCE

Packing format	Cartons on pallets
Carton packing	15 pcs/carton
Carton coverage	2.790 m²/carton (30.04 sq ft/carton)
Carton dimensions	317 × 625 × 62.0 mm (12.48 × 24.61 × 2.44 in)
Calculated carton net weight	22.33 kg/carton (49.22 lb/carton)
Calculated carton gross weight	22.83 kg/carton (50.32 lb/carton)
Pallet configuration	2 cartons/layer × 9 layers
Pallet packing	18 cartons / 270 panels per pallet
Loaded pallet dimensions	650 × 640 × 693.0 mm (25.59 × 25.20 × 27.28 in)
Pallet coverage	50.233 m²/pallet (540.71 sq ft/pallet)
Calculated pallet gross weight	441.87 kg/pallet (974.15 lb/pallet)
20 ft GP loading reference	56 pallets / 2813.076 m²/20 ft GP (30279.70 sq ft/20 ft GP)
20 ft GP cargo gross weight	24744.61 kg/20 ft GP (54552.52 lb/20 ft GP)