SPC WALL TILE | 4.0 MM | 0.20 MM WEAR LAYER | 406 × 812 MM

PREMIUM • SKU EF-WT-PRE40-020-406812 • INTERIOR WALL USE

Prepared by Ecoflors Technical Team • Version 2026.11.04-R01 • ecoflors.com

PRODUCT SPECIFICATION

Product type	SPC Wall Tile
Product format	Wall tile
Intended application	Interior decorative wall covering
Dimensions	406 × 812 mm (15.98 × 31.97 in)
Panel area	0.3297 m²/panel (3.55 sq ft/panel)
Total thickness	4.0 mm
Wear layer	0.20 mm (≈8 mil)
Construction	UV coating + 0.20 mm wear layer + décor film + SPC rigid core
Edge profile	Straight edge standard; 2-side T&G optional
Installation method	Glue-down installation (straight edge and optional T&G)
Calculated panel net mass	2.64 kg/panel (5.81 lb/panel)

PACKING & LOADING REFERENCE

Packing format	Cartons on pallets
Carton packing	8 pcs/carton
Carton coverage	2.637 m²/carton (28.39 sq ft/carton)
Carton dimensions	418 × 827 × 34.0 mm (16.46 × 32.56 × 1.34 in)
Calculated carton net weight	21.10 kg/carton (46.52 lb/carton)
Calculated carton gross weight	21.60 kg/carton (47.62 lb/carton)
Pallet configuration	2 cartons/layer × 16 layers
Pallet packing	32 cartons / 256 panels per pallet
Loaded pallet dimensions	860 × 840 × 679.0 mm (33.86 × 33.07 × 26.73 in)
Pallet coverage	84.396 m²/pallet (908.43 sq ft/pallet)
Calculated pallet gross weight	715.17 kg/pallet (1576.68 lb/pallet)
20 ft GP loading reference	34 pallets / 2869.465 m²/20 ft GP (30886.67 sq ft/20 ft GP)
20 ft GP cargo gross weight	24315.72 kg/20 ft GP (53606.99 lb/20 ft GP)