SPC WALL TILE | 4.0 MM | 0.20 MM WEAR LAYER | 610 × 1220 MM

PREMIUM • SKU EF-WT-PRE40-020-6101220 • INTERIOR WALL USE

Prepared by Ecoflors Technical Team • Version 2026.11.04-R01 • ecoflors.com

PRODUCT SPECIFICATION

Product type	SPC Wall Tile
Product format	Wall tile
Intended application	Interior decorative wall covering
Dimensions	610 × 1220 mm (24.02 × 48.03 in)
Panel area	0.7442 m²/panel (8.01 sq ft/panel)
Total thickness	4.0 mm
Wear layer	0.20 mm (≈8 mil)
Construction	UV coating + 0.20 mm wear layer + décor film + SPC rigid core
Edge profile	Straight edge standard; 2-side T&G optional
Installation method	Glue-down installation (straight edge and optional T&G)
Calculated panel net mass	5.95 kg/panel (13.13 lb/panel)

PACKING & LOADING REFERENCE

Packing format	Cartons on pallets
Carton packing	3 pcs/carton
Carton coverage	2.232 m²/carton (24.03 sq ft/carton)
Carton dimensions	622 × 1235 × 14.0 mm (24.49 × 48.62 × 0.55 in)
Calculated carton net weight	17.86 kg/carton (39.38 lb/carton)
Calculated carton gross weight	18.36 kg/carton (40.48 lb/carton)
Pallet configuration	1 cartons/layer × 41 layers
Pallet packing	41 cartons / 123 panels per pallet
Loaded pallet dimensions	640 × 1250 × 709.0 mm (25.20 × 49.21 × 27.91 in)
Pallet coverage	91.536 m²/pallet (985.29 sq ft/pallet)
Calculated pallet gross weight	772.29 kg/pallet (1702.61 lb/pallet)
20 ft GP loading reference	32 pallets / 2929.171 m²/20 ft GP (31529.34 sq ft/20 ft GP)
20 ft GP cargo gross weight	24713.37 kg/20 ft GP (54483.65 lb/20 ft GP)