SPC WALL TILE | 3.0 MM | 0.20 MM WEAR LAYER | 305 × 610 MM

SELECT • SKU EF-WT-SEL30-020-305610 • INTERIOR WALL USE

Prepared by Ecoflors Technical Team • Version 2026.11.04-R01 • ecoflors.com

PRODUCT SPECIFICATION

Product type	SPC Wall Tile
Product format	Wall tile
Intended application	Interior decorative wall covering
Dimensions	305 × 610 mm (12.01 × 24.02 in)
Panel area	0.1860 m²/panel (2.00 sq ft/panel)
Total thickness	3.0 mm
Wear layer	0.20 mm (≈8 mil)
Construction	UV coating + 0.20 mm wear layer + décor film + SPC rigid core
Edge profile	Straight edge standard
Installation method	Glue-down installation
Calculated panel net mass	1.12 kg/panel (2.46 lb/panel)

PACKING & LOADING REFERENCE

Packing format	Cartons on pallets
Carton packing	21 pcs/carton
Carton coverage	3.907 m²/carton (42.06 sq ft/carton)
Carton dimensions	317 × 625 × 65.0 mm (12.48 × 24.61 × 2.56 in)
Calculated carton net weight	23.44 kg/carton (51.68 lb/carton)
Calculated carton gross weight	23.94 kg/carton (52.78 lb/carton)
Pallet configuration	2 cartons/layer × 8 layers
Pallet packing	16 cartons / 336 panels per pallet
Loaded pallet dimensions	650 × 640 × 655.0 mm (25.59 × 25.20 × 25.79 in)
Pallet coverage	62.512 m²/pallet (672.88 sq ft/pallet)
Calculated pallet gross weight	415.08 kg/pallet (915.09 lb/pallet)
20 ft GP loading reference	60 pallets / 3750.768 m²/20 ft GP (40372.93 sq ft/20 ft GP)
20 ft GP cargo gross weight	24904.61 kg/20 ft GP (54905.26 lb/20 ft GP)