SPC WALL TILE | 3.0 MM | 0.20 MM WEAR LAYER | 610 × 914 MM

SELECT • SKU EF-WT-SEL30-020-610914 • INTERIOR WALL USE

Prepared by Ecoflors Technical Team • Version 2026.11.04-R01 • ecoflors.com

PRODUCT SPECIFICATION

Product type	SPC Wall Tile
Product format	Wall tile
Intended application	Interior decorative wall covering
Dimensions	610 × 914 mm (24.02 × 35.98 in)
Panel area	0.5575 m²/panel (6.00 sq ft/panel)
Total thickness	3.0 mm
Wear layer	0.20 mm (≈8 mil)
Construction	UV coating + 0.20 mm wear layer + décor film + SPC rigid core
Edge profile	Straight edge standard
Installation method	Glue-down installation
Calculated panel net mass	3.35 kg/panel (7.37 lb/panel)

PACKING & LOADING REFERENCE

Packing format	Cartons on pallets
Carton packing	7 pcs/carton
Carton coverage	3.902 m²/carton (42.01 sq ft/carton)
Carton dimensions	622 × 929 × 23.0 mm (24.49 × 36.57 × 0.91 in)
Calculated carton net weight	23.42 kg/carton (51.62 lb/carton)
Calculated carton gross weight	23.92 kg/carton (52.73 lb/carton)
Pallet configuration	2 cartons/layer × 25 layers
Pallet packing	50 cartons / 350 panels per pallet
Loaded pallet dimensions	1260 × 940 × 710.0 mm (49.61 × 37.01 × 27.95 in)
Pallet coverage	195.139 m²/pallet (2100.46 sq ft/pallet)
Calculated pallet gross weight	1210.83 kg/pallet (2669.43 lb/pallet)
20 ft GP loading reference	20 pallets / 3902.780 m²/20 ft GP (42009.17 sq ft/20 ft GP)
20 ft GP cargo gross weight	24216.68 kg/20 ft GP (53388.64 lb/20 ft GP)