SPC WALL TILE | 5.0 MM | 0.20 MM WEAR LAYER | 406 × 812 MM

SIGNATURE • SKU EF-WT-SIG50-020-406812 • INTERIOR WALL USE

Prepared by Ecoflors Technical Team • Version 2026.11.04-R01 • ecoflors.com

PRODUCT SPECIFICATION

Product type	SPC Wall Tile
Product format	Wall tile
Intended application	Interior decorative wall covering
Dimensions	406 × 812 mm (15.98 × 31.97 in)
Panel area	0.3297 m²/panel (3.55 sq ft/panel)
Total thickness	5.0 mm
Wear layer	0.20 mm (≈8 mil)
Construction	UV coating + 0.20 mm wear layer + décor film + SPC rigid core
Edge profile	Straight edge standard; 2-side T&G optional
Installation method	Glue-down installation (straight edge and optional T&G)
Calculated panel net mass	3.30 kg/panel (7.27 lb/panel)

PACKING & LOADING REFERENCE

Packing format	Cartons on pallets
Carton packing	7 pcs/carton
Carton coverage	2.307 m²/carton (24.84 sq ft/carton)
Carton dimensions	418 × 827 × 37.0 mm (16.46 × 32.56 × 1.46 in)
Calculated carton net weight	23.08 kg/carton (50.88 lb/carton)
Calculated carton gross weight	23.58 kg/carton (51.98 lb/carton)
Pallet configuration	2 cartons/layer × 15 layers
Pallet packing	30 cartons / 210 panels per pallet
Loaded pallet dimensions	860 × 840 × 690.0 mm (33.86 × 33.07 × 27.17 in)
Pallet coverage	69.231 m²/pallet (745.20 sq ft/pallet)
Calculated pallet gross weight	732.31 kg/pallet (1614.47 lb/pallet)
20 ft GP loading reference	34 pallets / 2353.858 m²/20 ft GP (25336.72 sq ft/20 ft GP)
20 ft GP cargo gross weight	24898.58 kg/20 ft GP (54891.97 lb/20 ft GP)