SPC WALL TILE | 5.0 MM | 0.20 MM WEAR LAYER | 457 × 914 MM

SIGNATURE • SKU EF-WT-SIG50-020-457914 • INTERIOR WALL USE

Prepared by Ecoflors Technical Team • Version 2026.11.04-R01 • ecoflors.com

PRODUCT SPECIFICATION

Product type	SPC Wall Tile
Product format	Wall tile
Intended application	Interior decorative wall covering
Dimensions	457 × 914 mm (17.99 × 35.98 in)
Panel area	0.4177 m²/panel (4.50 sq ft/panel)
Total thickness	5.0 mm
Wear layer	0.20 mm (≈8 mil)
Construction	UV coating + 0.20 mm wear layer + décor film + SPC rigid core
Edge profile	Straight edge standard; 2-side T&G optional
Installation method	Glue-down installation (straight edge and optional T&G)
Calculated panel net mass	4.18 kg/panel (9.21 lb/panel)

PACKING & LOADING REFERENCE

Packing format	Cartons on pallets
Carton packing	5 pcs/carton
Carton coverage	2.088 m²/carton (22.48 sq ft/carton)
Carton dimensions	469 × 929 × 27.0 mm (18.46 × 36.57 × 1.06 in)
Calculated carton net weight	20.88 kg/carton (46.04 lb/carton)
Calculated carton gross weight	21.38 kg/carton (47.15 lb/carton)
Pallet configuration	2 cartons/layer × 21 layers
Pallet packing	42 cartons / 210 panels per pallet
Loaded pallet dimensions	960 × 940 × 702.0 mm (37.80 × 37.01 × 27.64 in)
Pallet coverage	87.716 m²/pallet (944.17 sq ft/pallet)
Calculated pallet gross weight	917.17 kg/pallet (2022.00 lb/pallet)
20 ft GP loading reference	27 pallets / 2368.347 m²/20 ft GP (25492.68 sq ft/20 ft GP)
20 ft GP cargo gross weight	24763.48 kg/20 ft GP (54594.12 lb/20 ft GP)