SPC WALL TILE | 5.0 MM | 0.20 MM WEAR LAYER | 610 × 914 MM

SIGNATURE • SKU EF-WT-SIG50-020-610914 • INTERIOR WALL USE

Prepared by Ecoflors Technical Team • Version 2026.11.04-R01 • ecoflors.com

PRODUCT SPECIFICATION

Product type	SPC Wall Tile
Product format	Wall tile
Intended application	Interior decorative wall covering
Dimensions	610 × 914 mm (24.02 × 35.98 in)
Panel area	0.5575 m²/panel (6.00 sq ft/panel)
Total thickness	5.0 mm
Wear layer	0.20 mm (≈8 mil)
Construction	UV coating + 0.20 mm wear layer + décor film + SPC rigid core
Edge profile	Straight edge standard; 2-side T&G optional
Installation method	Glue-down installation (straight edge and optional T&G)
Calculated panel net mass	5.58 kg/panel (12.29 lb/panel)

PACKING & LOADING REFERENCE

Packing format	Cartons on pallets
Carton packing	4 pcs/carton
Carton coverage	2.230 m²/carton (24.01 sq ft/carton)
Carton dimensions	622 × 929 × 22.0 mm (24.49 × 36.57 × 0.87 in)
Calculated carton net weight	22.30 kg/carton (49.17 lb/carton)
Calculated carton gross weight	22.80 kg/carton (50.27 lb/carton)
Pallet configuration	2 cartons/layer × 26 layers
Pallet packing	52 cartons / 208 panels per pallet
Loaded pallet dimensions	1260 × 940 × 707.0 mm (49.61 × 37.01 × 27.83 in)
Pallet coverage	115.968 m²/pallet (1248.27 sq ft/pallet)
Calculated pallet gross weight	1199.68 kg/pallet (2644.85 lb/pallet)
20 ft GP loading reference	20 pallets / 2319.366 m²/20 ft GP (24965.45 sq ft/20 ft GP)
20 ft GP cargo gross weight	23993.66 kg/20 ft GP (52896.97 lb/20 ft GP)