SPC XL WALL PANEL | 3.0 MM | 0.20 MM WEAR LAYER | 1200 × 2800 MM

SELECT • SKU EF-WX-SEL30-020-12002800 • INTERIOR WALL USE

Prepared by Ecoflors Technical Team • Version 2026.11.04-R01 • ecoflors.com

PRODUCT SPECIFICATION

Product type	SPC XL Wall Panel
Product format	XL wall panel
Intended application	Interior decorative wall covering
Dimensions	1200 × 2800 mm (47.24 × 110.24 in)
Panel area	3.3600 m²/panel (36.17 sq ft/panel)
Total thickness	3.0 mm
Wear layer	0.20 mm (≈8 mil)
Construction	UV coating + 0.20 mm wear layer + décor film + SPC rigid core
Edge profile	Straight edge standard
Installation method	Glue-down installation
Calculated panel net mass	20.16 kg/panel (44.45 lb/panel)

PACKING & LOADING REFERENCE

Packing format	Direct on pallet; no carton
Pallet packing	97 panels/pallet
Loaded pallet dimensions	1220 × 2820 × 426.0 mm (48.03 × 111.02 × 16.77 in)
Pallet coverage	325.920 m²/pallet (3508.17 sq ft/pallet)
Calculated pallet net weight	1955.52 kg/pallet (4311.18 lb/pallet)
Calculated pallet gross weight	1995.52 kg/pallet (4399.37 lb/pallet)
20 ft GP loading reference	6 pallets / 1955.520 m²/20 ft GP (21049.04 sq ft/20 ft GP)
20 ft GP cargo gross weight	11973.12 kg/20 ft GP (26396.21 lb/20 ft GP)