SPC XL WALL PANEL | 3.0 MM | 0.20 MM WEAR LAYER | 900 × 2800 MM

SELECT • SKU EF-WX-SEL30-020-9002800 • INTERIOR WALL USE

Prepared by Ecoflors Technical Team • Version 2026.11.04-R01 • ecoflors.com

PRODUCT SPECIFICATION

Product type	SPC XL Wall Panel
Product format	XL wall panel
Intended application	Interior decorative wall covering
Dimensions	900 × 2800 mm (35.43 × 110.24 in)
Panel area	2.5200 m²/panel (27.13 sq ft/panel)
Total thickness	3.0 mm
Wear layer	0.20 mm (≈8 mil)
Construction	UV coating + 0.20 mm wear layer + décor film + SPC rigid core
Edge profile	Straight edge standard
Installation method	Glue-down installation
Calculated panel net mass	15.12 kg/panel (33.33 lb/panel)

PACKING & LOADING REFERENCE

Packing format	Direct on pallet; no carton
Pallet packing	129 panels/pallet
Loaded pallet dimensions	920 × 2820 × 522.0 mm (36.22 × 111.02 × 20.55 in)
Pallet coverage	325.080 m²/pallet (3499.13 sq ft/pallet)
Calculated pallet net weight	1950.48 kg/pallet (4300.07 lb/pallet)
Calculated pallet gross weight	1990.48 kg/pallet (4388.26 lb/pallet)
20 ft GP loading reference	12 pallets / 3900.960 m²/20 ft GP (41989.58 sq ft/20 ft GP)
20 ft GP cargo gross weight	23885.76 kg/20 ft GP (52659.09 lb/20 ft GP)