SPC XL WALL PANEL | 5.0 MM | 0.20 MM WEAR LAYER | 900 × 2800 MM

SIGNATURE • SKU EF-WX-SIG50-020-9002800 • INTERIOR WALL USE

Prepared by Ecoflors Technical Team • Version 2026.11.04-R01 • ecoflors.com

PRODUCT SPECIFICATION

Product type	SPC XL Wall Panel
Product format	XL wall panel
Intended application	Interior decorative wall covering
Dimensions	900 × 2800 mm (35.43 × 110.24 in)
Panel area	2.5200 m²/panel (27.13 sq ft/panel)
Total thickness	5.0 mm
Wear layer	0.20 mm (≈8 mil)
Construction	UV coating + 0.20 mm wear layer + décor film + SPC rigid core
Edge profile	Straight edge standard; 2-side T&G optional
Installation method	Glue-down installation (straight edge and optional T&G)
Calculated panel net mass	25.20 kg/panel (55.56 lb/panel)

PACKING & LOADING REFERENCE

Packing format	Direct on pallet; no carton
Pallet packing	77 panels/pallet
Loaded pallet dimensions	920 × 2820 × 520.0 mm (36.22 × 111.02 × 20.47 in)
Pallet coverage	194.040 m²/pallet (2088.63 sq ft/pallet)
Calculated pallet net weight	1940.40 kg/pallet (4277.85 lb/pallet)
Calculated pallet gross weight	1980.40 kg/pallet (4366.03 lb/pallet)
20 ft GP loading reference	12 pallets / 2328.480 m²/20 ft GP (25063.55 sq ft/20 ft GP)
20 ft GP cargo gross weight	23764.80 kg/20 ft GP (52392.42 lb/20 ft GP)